

WARNING:

DO NOT INSTALL YOUR NEW COUPLER LOCK UNTIL YOU HAVE READ THE FOLLOWING:

CARE & USE INSTRUCTIONS

(1) To install your new coupler lock: First insert the lock base uni-ball into your trailer coupler ball receiving area, then insert the U shaped locking bar. Once the locking bar has been partially inserted, turn the key to the middle dot, or ratchet position, then lightly push the locking bar down into the lock base. You should here a clicking noise if the key is in the correct middle dot position. Once the locking bar is lightly touching the top of your trailers coupler, slowly remove the key from the lock. If The key feels like it does not want to come out of the lock cylinder easily, please try to adjust the lock into a less clamped position until the key comes out of the lock without forcing it. Forcing the key out of the lock cylinder before the teeth on the locking bar are lined up properly with the teeth on the two internal slide rods will damage your lock and void the manufacturers warranty.

(2) You can use most light weight oils or spray type lithium grease products to lubricate the internal slide rods within your lock, but never use WD-40 or other types of penetrating oils to lubricate your lock. If these products are needed to clean the lock, they must be blown completely out of the lock and then oil must be poured back into the slide pin rods for proper lubrication of the internal components.

Limited Warranty

Diversi-Tech Corporation USA warrants each coupler lock to be free from defects in workmanship and materials for the life of the product when operated and maintained under normal conditions (Excluding Chrome and Corrosion). The use of WD-40 or other penetrating oils as a lubricant for your lock will void the manufacturers warranty and cause severe damage to the lock. The use of such products will deplete the internal lubricants, resulting in problems that could damage the internal parts when the key is forced to try to overcome the lock up problem caused by the penetrating oil. Coupler locks used in freezing rain areas of the country that have been forced to open while frozen will not be covered under this warranty. Coupler locks returned without keys or without the correct keys will not be considered for warranty claim. Coupler locks that have been stripped out due to forcing the key out of the coupler locks lock cylinder before the teeth on the lock bar are aligned properly with the teeth on the locking pins will not be covered. Locks that have been backed into by a drop hitch, hammered off, or cut off during a theft attempt will also not be covered by this limited warranty. All security products can be defeated by an aggressive thief. This product is only intended to deter theft attempts. If you notice a valid defect or problem within the first ten (10) days after your initial purchase date, please simply return the coupler lock to your dealer for a free replacement. If you notice a defect with your coupler lock after the first ten days, do not return it to your dealer, you must go to www.diversi-tech.net and select the contact us tab, and then select the service/warranty option on the contact us form page. Once submitted, please allow one business day for someone to contact you with warranty return instructions. Customer will be responsible for all costs associated with returning the product for repair or replacement.